



# STUCCO CAULK

Cal Dorado Stucco Caulk is a texturized silicon acrylic caulk for the maintenance of stucco finishes. Cal Dorado Stucco Caulk is pre-blended to match each of our colors.

## **SURFACE PREPARATION**

All surfaces must be free of debris, dirt and dust, grease, oils, curing agents, and cleaning solutions. Glossy or painted surfaces must be sanded and cleaned to ensure a proper bond.

## **DIRECTIONS**

1. Knead tube until soft.
2. Cut tip off at an angle.
3. Completely fill cracks with sealer.
4. Smooth with wet finger.

## **CURING**

Cal Dorado Stucco Caulk should fully cure in 24 hours. Curing time may vary due to ambient temperature or thickness of material.

## **CLEANING**

Clean all tools with water immediately after use.

## **COVERAGE**

Coverage will vary depending on application method. Approximate coverage per 10.2 fl. oz. (301 ml) tube: 50 - 55 linear ft. (3/16" bead).

## **PACKAGING**

- Cal Dorado stucco caulk is packaged in 10.2 fl. oz. (301 ml) tubes.
- 30 colors to choose from.

## **LIMITATIONS**

Do not apply Cal Dorado stucco caulk when the ambient and surface temperature is below 50°F/10°C. Do not apply to substrates which are frozen or contain frost/ice. Do not add any other materials to the mixture of Cal Dorado stucco caulk. Failure to follow these instructions could result in cracking, chipping, discoloration, or peeling. Due to job conditions beyond the control of Western States Wholesale, Inc. we make no warranty as to the acceptance of the final color.

## **SAFETY**

Wear rubber gloves and eye protection. Avoid eye contact or prolonged contact with skin. If eye contact occurs, flush with water for 15 minutes. Consult physician immediately.

**KEEP OUT OF REACH OF CHILDREN.  
DO NOT TAKE INTERNALLY.**