



## PRODUCT DESCRIPTION

ProActive™ is a Portland cement based, pre-blended underlayment for use on interior and exterior floors prior to the installation of ceramic tile, natural stone, vinyl flooring, carpet, wood, parquet. Can be applied up to 1" (25.4 mm) thick in one pour. Seeks its own level in minutes. Just add water and mix — no blending of powders required!

### AREAS OF USE

- Concrete Slab

### USE UNDER THESE FLOOR COVERINGS

- Ceramic tile, pavers, brick
- Stone
- Carpet
- Wood, parquet
- Vinyl flooring
- Laminated flooring

### LIMITATIONS

Do not use over lightweight concrete, gypsum underlayments, particle board, hardwood floors, parquet floors, or metal. Do not use when temperature is below 50°F (10°C). ProActive is not meant for use as a wear surface.

### SURFACE PREPARATION

Surface must be dry and free from dirt, oil and other contaminants that will prevent a good bond. Surface must be treated with **ProActive Primer™**. Surface temperature must be between 50°F (10°C) and 100°F (38°C). Concrete must be fully cured before ProActive is applied.

### MIXING

Mix 50 lb. (22.68 kg) bag of ProActive powder with 6 1/2 quarts (6.1 L) of clean, cool water. Slowly add powder to water while mixing. Continue mixing for 2 minutes to a lump-free, pourable consistency.

### APPLICATION

Pour or pump, then spread with a long-handled gauged spreader. Will seek its own level during the first 20 minutes. For feathered edging and touch-ups, use a smoothing tool. Can be applied up from 3/8" to 1" (9.525 – 25.4 mm) thick in one application.

If a second layer is required, install immediately after the first layer has set to a walkable hardness. If the first layer has dried over 12 hours, re-prime before second application. Temperature may vary working conditions.

### CURING

Dries to a walkable hardness in 2–4 hours. Allow 4 hours cure time for ceramic tile and stone; 16 hours for other floor coverings. Drying time can vary with temperature and humidity.

### CLEAN-UP

Clean with water before material dries.

### COVERAGE

Approx. 40 sq. ft. per 50 lb. bag depending on depth of application.

### PACKAGING

- 50 LBS. (22.7 KG) Bag

### STORAGE

Store in a cool dry area. Keep from freezing.

### SAFETY

Contains Portland cement. Wear rubber gloves and eye protection. Avoid eye contact or prolonged contact with skin. If eye contact occurs, flush with water for 15 minutes. Consult physician immediately.

KEEP OUT OF REACH OF CHILDREN.

DO NOT TAKE INTERNALLY.

### WARNING

Western States Wholesale, as blender of processed material in the State of California, we are required by Proposition 65 to warn that one or more of the components in this product, contains chemicals known to the State of California, to cause cancer, birth defects, or other reproductive harm.