



ProDUCTIVE

FAST SETTING THIN-SET MORTAR

PRODUCT DESCRIPTION

ProDuctive™ is a fast-setting mortar specially formulated for time critical installations. ProDuctive cures rapidly – you can grout in just 2 hours! Excellent for commercial use in hotels, restaurants and malls where timely installations are a must. Works well for homeowner tile repairs and smaller jobs where you don't want to wait. ProDuctive is used for setting porous ceramic tile. ProDuctive can be mixed with water or an acrylic additive, like **ProCure**™ for setting non-porous tiles.

AREAS OF USE

- Interior or exterior floors, walls, and countertops
- Concrete, mortar beds, masonry
- Cement backerboards

LIMITATIONS

Do not apply to wood, asphalt sheeting, vinyl wallboard, metal, glass, gypsum mortar beds or gypsum-based underlayments.

APPLICABLE STANDARDS

Meets or exceeds ANSI A118.1 for dry-set mortars

SURFACE PREPARATION

Surface must be dry and free from dirt, oil and other contaminants that will prevent a good bond. Glossy or painted surfaces must be sanded and cleaned. Surface temperature must be between 50°F (10°C) and 100°F (38°C). Concrete must be fully cured before ProDuctive is applied.

MIXING

Thoroughly mix 3 quarts (2.84 L) clean, cool water and a 25 lb. (11.3 kg) bag of ProDuctive mortar together and mix to a smooth, paste-like consistency. Let stand for 5–10 minutes, stir again and use. Stir occasionally to keep workable, but do not add more water. When properly mixed, troweled ridges will stand firm.

APPLICATION

Using the flat side of trowel, apply skim coat of mortar to the surface. Apply additional mortar with notched side of

trowel held at a 45° angle to the surface, combing in one direction. Press tile firmly into place. Adjust tile promptly. Do not spread more material than can be tiled in 5 minutes or while material is still sticky to the touch. If mortar dries, remove and replace with fresh material. Material in bucket will remain workable for up to 30 minutes. Temperatures may vary working conditions.

CURING

Allow to cure for 2–4 hours before grouting, depending upon temperature and humidity. Allow an additional 3–4 hours before heavy traffic.

CLEAN-UP

Clean with soap and water.

COVERAGE

30–45 sq. ft. per 25 lb. bag when applied with 1/4" X 1/4" square-notched trowel.

PACKAGING

- 25 LBS. (11.3 KG) Bag
- Gray only

STORAGE

Store in a cool dry area. Keep from freezing.

SAFETY

Contains Portland cement. Wear rubber gloves and eye protection. Avoid eye contact or prolonged contact with skin. If eye contact occurs, flush with water for 15 minutes. Consult physician immediately. This product contains free silica. Do not breathe dust; wear NIOSH approved respirator. KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.

WARNING

Western States Wholesale, as blender of processed material in the State of California, we are required by Proposition 65 to warn that one or more of the components in this product, contains chemicals known to the State of California, to cause cancer, birth defects, or other reproductive harm.

AVERAGE COVERAGE PER 25 LB. (11.3 KG) BAG

	1/4" X 1/4" (6.4 mm X 6.4mm)	1/4" X 3/8" (6.4 mm X 6.4mm)	1/2" X 1/2" (6.4 mm X 6.4mm)
Product	Square-notched Trowel	Square-notched Trowel	Square-notched Trowel
ProDuctive	44 Sq. Ft. (4.8 M ²)	38 Sq. Ft. (3.53 M ²)	23 Sq. Ft. (2.14 M ²)

* These measurements are approximate. Actual coverage may vary due to prevailing conditions.