

**MANUFACTURED FOR**

Western States Wholesale
1420 S. Bon View, Ontario, CA 91761
Emergency Phone: (800) 325-6851

SECTION I – Identity

ProTect

**SECTION II – Hazardous Ingredients/
Identity Information**

Component: Styrene butadiene Co-polymer/water dispersion (CAS# Proprietary)
OSHA PEL: Not Established
ACGIH TLV: Not Established. Not a hazardous material as defined in title 29 CFR parts 1900 to 1910.

SECTION III**Physical/Chemical Characteristics**

Boiling Point: 100° C (212° F)
Specific Gravity: 1.08 -1.14
Vapor Pressure: 17.5 mg Hg @70° F
Melting Point: N/A
Solubility in water: Dispersible
Vapor Density: Heavier than Air
Evaporation Rate :< 1(Butyl/acetate=1)
Appearance and Odor: Bright red viscous- bland odor.

SECTION IV**Fire and Explosion Hazard Data**

Flash Point: N/A
Flammable Limits: N/A
Extinguishing Media: N/A
Special Fire Fighting Procedures: Water fog-dried resin only.
Unusual Fire and explosion Hazards: As latex, material's not combustible; however, the dried resin is combustible similar to wood. Burning dry resin emits dense black smoke.
Fire fighting equipment: Wear positive self contained breathing apparatus.

SECTION V - Reactivity Data

Stability: Stable
Incompatibility: Not known.
Hazardous Decomposition or by-products: If dried film burns, it produces carbon monoxide and low molecular-weight organic compounds.
Hazardous Polymerization: Will Not Occur.
Conditions to avoid: Keep from freezing.

SECTION VI - Health Hazard Data**Primary Routes of Entry:**

Inhalation-YES

Skin-YES

Ingestion-NO

Health Hazards:

Acute: Vapor or mist can cause headache, nausea and irritation of the nose, throat, and lungs. Irritation to skin upon repeated or prolonged contact. Slightly irritating eyes.

Carcinogenicity:

This product does not contain 0.1% or more of any substance listed as a carcinogen by NTP, IARC or OSHA.

Signs and symptoms of exposure: Reddening of eyes and skin upon contact.

Medical Conditions Aggravated by Exposure: Hypersensitive individuals may develop allergic dermatitis.

Emergency and First Aid procedures: Inhalation: Move subject to fresh air. Eye and Skin contact: Flush eyes with large amount of water for at least 15 minutes. See physician if irritation persists, wash affected skin areas with soap and water. If accidentally ingested, contact a physician.

SECTION VII**Precautions for Safe Handling and Use**

Released or Spilled: Floor will be slippery, use caution. Clean with water before allowing to dry. Sodium chloride may help to coagulate waste to containers for disposal. Wear protective equipment during cleanup.

Waste Disposal Method: Material, its containers and waste should be disposed off in an approved facility in accordance with current federal, state, and local regulations.

Precautions to be taken in handling and storing: Keep from freezing, keep temperature below 100° C.

SECTION VIII - Control Measures

Respiratory Protection: Not required if good ventilation maintained. Wear OSHA mask for chemical vapors. OSHA approved mask for chemical vapors.

Ventilation: General ventilation is recommended during normal use.

Protective Gloves: Chemicalresistant nitrile, neoprene or rubber gloves required.

Eye Protection: Wear face shield or chemical splash goggles.

Other Protective Clothing: Barrier cream, boots and clothing should protect skin from direct contact with product.

Work/Hygienic Practices: Shower with soap and water after working with this product.

NA= NOT APPLICABLE

C= CENTIGRADE

F= FAHRENHEIT

DATE REVISED: 3/02/05

Disclaimer

The information presented is believed to be accurate but is not warranted to be. Whether originating with the company or not. Recipients are advised to confirm in advance of need, that the information is current, applicable and suitable to their circumstance.